

ZESTAWIENIE STALI DO RYS. K-1

| Numer | Średnica | Ilość w 1 elem. | Długość 1 szt. | Długość całkowita | Długość ogólna | | | |
|-----------------------------------|----------|--------------------|-------------------|----------------------|----------------|-------|--------|-------|
| | | | | | St0S-b | St3SX | 18G2-b | 34GS |
| | | | | | φ6 | φ8 | φ10 | φ12 |
| | [mm] | [szt.] | [mm] | [m] | [m] | [m] | [m] | [m] |
| 1 | 8 | 2 | 2510 | 5,02 | | 5,02 | | |
| 2 | 8 | 2 | 3300 | 6,60 | | 6,60 | | |
| 3 | 8 | 2 | 4560 | 9,12 | | 9,12 | | |
| 4 | 8 | 2 | 5815 | 11,63 | | 11,63 | | |
| 5 | 8 | 2 | 6495 | 12,99 | | 12,99 | | |
| 6 | 8 | 2 | 6870 | 13,74 | | 13,74 | | |
| 7 | 10 | 2 | 2500 | 5,00 | | | 5,00 | |
| 8 | 10 | 8 | 2474 | 19,79 | | | 19,79 | |
| 9 | 10 | 8 | 2410 | 19,28 | | | 19,28 | |
| 10 | 10 | 8 | 1082 | 8,66 | | | 8,66 | |
| 11 | 12 | 2 | - | 28,75 | | | | 28,75 |
| 12 | 12 | 2 | - | 27,95 | | | | 27,95 |
| 13 | 12 | 2 | - | 27,20 | | | | 27,20 |
| 14 | 6 | 106 | 1040 | 110,24 | 110,24 | | | |
| 15 | 6 | 130 | 740 | 96,20 | 96,20 | | | |
| 16 | 12 | 4 | 160 | 0,64 | | | | 0,64 |
| 17 | 10 | 8 | 1585 | 12,68 | | | 12,68 | |
| 18 | 8 | 7 | 2510 | 17,57 | | 17,57 | | |
| Długość ogólna [m] | | | | | 206,44 | 76,67 | 65,41 | 84,54 |
| Masa 1m pręta [kg] | | | | | 0,222 | 0,395 | 0,617 | 0,888 |
| Masa prętów wg średnic [kg] | | | | | 45,83 | 30,28 | 40,36 | 75,07 |
| Masa prętów wg gatunku stali [kg] | | | | | 45,83 | 30,28 | 40,36 | 75,07 |
| Masa całkowita prętów [kg] | | | | | 191,54 | | | |